

Feature Comparision – XPort Direct & XPort

| Features | XPort Direct | XPort XPort Direct+ |
|--------------------------------|-------------------------------------|-------------------------------------|
| <i>Protocol Support</i> | | |
| TCP | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> |
| UDP client-server | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> |
| ICMP | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> |
| Telnet | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> |
| ARP | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> |
| DHCP | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> |
| BOOTP & AUTOIP | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> |
| TFTP | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> |
| SNMP | | <input checked="" type="checkbox"/> |
| Web Server (HTTP) | | <input checked="" type="checkbox"/> |
| Java Applets or Scripts | | <input checked="" type="checkbox"/> |
| Password Protection | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> |

| Features | XPort Direct | XPort XPort Direct+ |
|--|-------------------------------------|-------------------------------------|
| <i>Modem Signals</i> | | |
| RTS, CTS, DTR, DCD/Modem Control Input | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> |
| <i>General Purpose I/O</i> | 2 | 3 |
| <i>AES encryption</i> | | <input checked="" type="checkbox"/> |
| <i>Modem mode</i> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> |
| <i>Manual mode</i> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> |
| CPK (Software Development Kit) | | <input checked="" type="checkbox"/> |
| | | |
| <i>Flash</i> | 128K | 512K |
| <i>Maximum Serial Throughput</i> | 230 Kbps | 921 Kbps |
| <i>WebManager</i> | | <input checked="" type="checkbox"/> |
| <i>Email Client</i> | | <input checked="" type="checkbox"/> |
| <i>Operating Temperature</i> | 0 to 70C | -40 to 85C and 0 to 70C |



1630 Diehl Road
 Naperville, Illinois 60563 USA
 +1 630 245-1445, +1 630 245-1717 FAX